


SPRAY PAINT PB101

Description:

Acrylic-based aerosol paint colored according to RAL standard, ideal for painting scratches and dents formed during mounting of metal tiles and other types of roofing. Full color match. Also, can be used for painting metal, wood, plastics, stone and concrete. Protects against corrosion, weather and wear resistant.

Physical Properties	
Appearance	Colored Aerosol
Color	customized
Odour	Pugent odor
Melting point/freezing point (°C)	Minus 96 °C
Boiling point, initial boiling point (°C)	105 °C
Relative density(H ₂ O=1)	1.03±0.02
Vapor pressure (20°C) (kPa)	3.1
Flash point (°C)	4 °C
Viscosity (mPa.S)	N/A
Explosive limit - lower (%)	4.5 vol%
Solubility in water	Not soluble in water
Solubility in organic solvents	Soluble in most organic solvents such as benzene, alcohol and ether
Film Properties	
Drying time min	10Minutes
Thickness	0.2millimetre(Spraying 2 times)
Hardness	Shore A
Adhesion on metal	Excellent
steadiness	N/A

Work Instruction	
 1	The object must be kept clean and dry, shake for one minute before using
 2	keep 10-20cm between the nozzle and the object surface
 3	Spray the spray paint thinly back and forth once
 4	keep in a cool or dry place
 5	Cannot be placed upside down

Products	Package(PCS/CTN)	Storability at 25° C (month)
SPRAY PAINT	12PCS/CARTON	36

Safety Information

- 1,Not use or store near the fire
- 2,Do not hit, the can is non-recycle
- 3,MSDS is available at distributors or the manufacture

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.