

Technical Data Sheet

TYPE: PB113

Revision Date: 20 June 2023
TDS no.: 22-01-035

Technical Data Sheet

QUICK START

Description:

- 1, Made with advanced formula
- 2, Make the diesel engine start quickly in low temperature (above -40°C) in 1-15 seconds without being preheated

Physical Properties	
Appearance	liquid
Color	Slightly yellow transparent clear liquid
Odour	Dichloromethane
Relative density (water=1)	0.70~0.73
Boiling point ($^{\circ}\text{C}$)	>35
melting point ($^{\circ}\text{C}$)	-116.2
Flash point ($^{\circ}\text{C}$)	<0
Ignition temperature ($^{\circ}\text{C}$)	160
Upper explosion limit [% (V/V)]	36
Lower explosion limit [% (V/V)]	1.9
Water Solubility	slightly soluble in water and soluble in most organic solvents such as ethanol, benzene, chloroform, etc

Work Instruction
Shake well before use
Remove air cleaner and spray into the air inlet for 3-5 seconds, do not spill
Start engine again
Do not use when engine is running

Products	Package (PCS/CTN)	Storability at 25°C (month)
QUICK START	24PCS/CARTON	36

The strongest hold for the toughest material

Safety Information

1,Not use or store near the fire

2,Do not hit, the can is non-recycle

3,MSDS is available at distributors or the manufacture

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.

The strongest hold for the toughest material