

TYPE: PB84

Revision Date: 20 June 2023
TDS no.: 22-01-035

Technical Data Sheet

ANTI-RUST SPRAY LUBRICANT

- Description:**
- 1.Protects metal surface and loosens rusted fittings
 - 2.Lubricate moving parts and inhibits corrosion
 - 3.Halt squeaks and remove tar and grease.
 - 4.Drive out moisture

Physical Properties	
Appearance	liquid
Color	Yellow slightly cloudy
Odor	solvent odor
Relative density (water=1)	0.85±0.05
Boiling point (°C)	> 35
Upper explosion limit [% (V/V)]	4.8
Lower explosion limit [% (V/V)]	0.7
PH value	N/A
Kinematic viscosity	Not determined
Specific Gravity	Not determined
Flash point (°C)	N/A
Solubility	Insoluble in water and ethanol, soluble in organic solvents such as benzene and ether
Work Instruction	
Shake well before use.	
Saturate area to be treated and allow to soak	
For best protection, do not wipe off	

Products	Package(PCS/CTN)	Storability at 25° C (month)
ANTI-RUST SPRAY LUBRICANT	24PCS/CARTON	36

- Safety Information**
- 1,Not use or store near the fire
 - 2,Do not hit, the can is non-recycle

3,MSDS is available at distributors or the manufacture

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.

The strongest hold for the toughest material