Prime-Bond®
Multi Purpose Adhesives

AQH Import & Export (Pty) Ltd
t/a Prime-Bond

Technical Data Sheet

TYPE: PB86

Revision Date: 20 June 2023
TDS no.: 22-01-035

Technical Data Sheet

CARBURETOR CLEANER

Description: 1.Superior formula
2.Remove gum,vanish and carbon deposits effectively,by simply spray it directly into the carburetor.
3.Clean the entire system,lubricate and remove moisture in all moving parts.
4.Increase engine power, maintain high gas mileage

Physical Properties	
Appearance	Transparent liquid
Color	Transparent
Odor	Dichloromethane odor
PH value	7
Relative density (water=1)	1.04～1.06
Boiling point (℃)	＞35
melting point（℃）	Minus 96
Upper explosion limit [%(V/V)]	44
Lower explosion limit [%(V/V)]	2.5
Saturated vapor pressure (kPa)	13.83 （20℃）
Solubility	Insoluble in water , soluble in organic solvents such as benzene and alcohol, ether, etc

Work Instruction
Start the engine for 5-10 minutes
Remove the air cleaner. For the engine at fast idle(5000-6000rpm), spray the carb cleaner into the air-horn,flooding choke,throttle shafts and plates
Gums, Varnishes and Carbon Deposits will be burnt away through exhaust gases
Turn off the engine and install the air cleaner again
For the FUEL INJECTION systems, spray 1/2 can of this Carb Cleaner directly into 1/2 tank fuel

Products	Package(PCS/CTN)	Storability at 25° C (month)
CARBURETOR CLEANER	24PCS/CARTON	36

Safety Information

1,Not use or store near the fire

2,Do not hit, the can is non-recycle

3,MSDS is available at distributors or the manufacture

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.