

TYPE: PB89

Revision Date: 20 June 2023  
TDS no.: 22-01-035

Technical Data Sheet  
DIESEL INJECTION CLEANER

Description:  
1.Used to clean plugged diesel injector system and keep them clean.  
2.For diesel engines only

| Physical Properties          |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Appearance                   | Red liquid                                                           |
| Flash point ( °C )           | -4°C                                                                 |
| Melting point/freezing point | -98°C                                                                |
| Boiling point/boiling range  | 65°C                                                                 |
| Relative density (20°C)      | 0.79 ± 0.02                                                          |
| Odour                        | solvent                                                              |
| Solubility:                  | Miscible in most organic solvents such as benzene, alcohol and ether |

| Work Instruction                                                                  |
|-----------------------------------------------------------------------------------|
| Shake well before use                                                             |
| Fill into diesel tank                                                             |
| A second treatment maybe necessary for badly plugged systems,use every 5000 miles |

| Products                 | Package(PCS/CTN) | Storability at 25° C (month) |
|--------------------------|------------------|------------------------------|
| DIESEL INJECTION CLEANER | 12PCS/CARTON     | 36                           |

Safety Information

1,Not use or store near the fire

2,Do not hit, the can is non-recycle

3,MSDS is available at distributors or the manufacture

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.

**The strongest hold for the toughest material**