

Technical Data Sheet

TYPE: PB93

Revision Date: 20 June 2023

TDS no.: 22-01-035

Technical Data Sheet

MOTOR FLUSH

Description:

1. Remove sludge, varnish and gums.
2. Free from sticky valves and rings.
3. Help to improve and extend the engine of life
4. Allow oil to circulate freely.

Physical Properties

Appearance	liquid
Color	clear
Odour	Kerosene
Viscosity	N/A
Flash point	>60 °C (closed cup method)
Relative density (20°C)	0.75 ± 0.03
Soluble in water	Insoluble

Work Instruction

Before exchanging the oil, stop the engine firstly.
While it reaches normal temperature, inject the motor flush into engine under using direction
Start engine to work and then stop it after 3 minutes
Please keep cleaning longer if there are too much sediment inside, then set the old oil free and inject fresh oil

Products	Package(PCS/CTN)	Storability at 25° C (month)
MOTOR FLUSH	24PCS/CARTON	36

Safety Information

- 1, Not use or store near the fire

The strongest hold for the toughest material

2, Do not hit, the can is non-recycle

3, MSDS is available at distributors or the manufacture

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user.

The strongest hold for the toughest material